

RECEIVER OUTFIT	COMPONENT UNITS	NUMBER OF VALVES	FREQUENCY RANGE IN KILOCYCLES	SERVICE
CE	A4 M4 N9	4 NR14 3 NR14	1500 - 6000	Obsolete. Type 83 only
CF	M3B A5 M5 K5 N9 Board for Valve Det.	3 NR14 7 NR17 1 NR14 3 NR14 1 NR14	16 - 1800 450 - 2000 13.5 - 2500	N9 to Second Offices only. Obsolete
CG	A4 M4 N9 Board for Valve Det.	4 NR14 3 NR14 1 NR14	1500 - 6000	Type 43A. <u>Obsolet</u>
CH	A5 M5 N9	7 NR17 3 NR14	450 - 2000	Type 45 Obsolete
CI	A5 M5 A11 M11 K5 N9 M3B or Board for Valve Det.	7 NR17 4 NR17 1 NR14 3 NR14 3 NR14 1 NR14	450 - 2000 12 - 550 13.5 - 2500 16 - 1800	Obsolescent
CJ	A11 M11 K5 N9	4 NR17 1 NR14 3 NR14	12 - 550 13.5 - 2550	Obsolescent
CK	A9 M9 K5 N9 Board for Valve Det.	5 NR15A 1 NR14 3 NR14 1 NR14	60 - 670 13.5 - 2550	Submarines Obsolescent
CL	A5 M5 M9 N9 K5	7 NR17 5 NR15A 3 NR14 1 NR14	450 - 2000 60 - 670 13.5 - 2550	Second Office of Flotilla Leaders. Obsolete.
CM				Obsolete nomenclature. Ships fitted with CM should no report these components separately as CN, CO, CSC etc., (see over)
<u>CN</u> CNS	A19 M19  N19	D.C. - 2 NR23 1 - NR15A 1 - NR16A Or <u>A.C.</u> - 2 NR37 1 NR27 1 NR26 D.C. - 1 NR23 2 NR15A Or <u>A.C.</u> - 1 NR38 2 NR27	15 - 550	CNS: Shore Stations
CO COS	B12	1 NR22 or NR23 8 NR15 or NR15A	150 - 1500	COS: Shore Stations
CP CPS	B11 <u>Patt. 1206/k</u> Or <u>Patt 1265/k</u>	1 NR22 or NR23 3 NR15A	900 - 23,000	CPS: Shore Stations. *Not to submarines. A bracket bulkhead mounting is supplied with 1265K.
<u>CQ</u> CQS	B11	1 NR22 or NR23 3 NR15A	900 - 23,000	<u>CQS</u> : Shore Stations. Fitted in rack
CR				Obsolete nomenclature. Ships fitted with CR should now report these components separately as <u>CQ</u> , G31, etc.
CS	B13	3 NR15A	15 - 20,000	CS: <u>Typ 51</u> or 51L in
CSA CSC CSD CSS				existing small craft and in T.R. of " <u>WARSPITE</u> ".  CSA: Main office receiver in small craft and in T.R. of early ships fitted with <u>C.C.S.</u>  CSC: Stand-by receiver, rack mounted.  CSD: Stand-by receiver fitted in <u>bulkhead bracket</u> .  CSS: Fitted in Shore Stations.
<u>CSB</u>	B13	3 Army Type VR27	15 - 20,000	<u>CSB</u> : FITTED WITH TW12B as a separate line of communication.
CT	B15	4 NR41 3 NR42	3000 - 23,000	Shore Stations only.
<u>QK</u>	B6  N9	1 NR19 or NR22 1 NR15A 3 NR14	3500 - 20000	N9 not supplied to Flotilla Leaders. Obsolescent.
RA	B3	5 NR7	750 - 1500	Obsolete. Type 81 only
<u>CAA</u>	A50 M50	3 NR51 2 NR52	15 - 550	<u>A.C.</u> Supplies only.
CAB	A50 M50  B50	3 NR51 2 NR52 1 NR27 4 NR51 2 NR52	15 - 550 550 - 23000	<u>A.C.</u> Supplies only
CAC	A50 M50  B16	3 NR51 2 NR52 4 NR51 - 2 NR52	15 - 550 3000 - 23000	<u>A.C.</u> Supplies only R/T Receiver
		1 NR27 - 1 N.S.1		
CAD	B50	1 NR27 4 NR51 2 NR52	550 - 23000	<u>A.C.</u> Supplies only.
CAE	B50  B16	1 NR27 4 NR51 2 NR52 4 NR51 2 NR52 1 NR27 1 NR46 - N.S.1	550 - 23000 3000 - 23000	<u>A.C.</u> Supplies only. R/T Receiver.
<u>CBA</u>	B19	1 NR41 3 VR27	100 - 13500	Box mounted. Battery supplied as part of Type 60E
<u>CBB</u>	B19	1 NR41 3 VR27	100 - 13500	Rack mounted. Battery supplies as standard emrgency equipment.
<u>CUA</u>	B16	4 NR51 2 NR52 1 NR27 1 NR46 1 N.S.1	3000 - 23000	R/T Receiver. <u>A.C.</u> Supplies only
Marconi 352A	Receiver 352A	2 LP2	15 - 20000	Fitted in large sea going RFAs. (C.A.F.O. 783/37).
Marconi 384	Amplifier 384	1 VP21 1 X21	600 - 220 275 - 92 10	
Marconi 372	H/F Receiver Marconi 372	1 S215 1 HL210 1 PT235 Or 1 HL210	3000 - 21428	
Marconi Auto-Alarm	Receiver Type 332  Selector Type 333	2 <u>DER</u> 1 DE7	505 - 615	
Marconi 394E	Receiver Type 394E	2 ARS8 1 NR39 1 NR42 1 ND3	150 - 3000	Used with TW12A and TW12B in small craft. 150 volts required for anodes of valves.
Marconi 394F	Receiver Type 394F	2 ARS8 1 ARP4 1 NT82	150 - 4200	Used with TW12/A/B/C in small craft.
Marconi	521 352A 560 372 596		3750 - 21428 15 - 20000 15 - 25500 3000 - 20000 15 - 20000	
<u>IMRC</u>	RM3		3529 - 20000	
<u>IMRC</u>	RM4		150 - 2500	
<u>IMRC</u>	RM5B		15 - 20000	
<u>IMRC</u>	RM14		150 - 2727	
<u>IMRC</u>	RM15		15 - 21500	